

portable pneumatic cold fogging unit



Optional adjustable nozzle

Standard accessories:

Shoulder strap Solution funnel Double air filter Dosing nozzle size 7, 8, 10

sealing rings

Optional accessories:

Adjustable nozzle 15 m power cable Storage box

Technical Data:

Packing dimensions (length x breadth x height):

Weight:

Capacity of solution tank :

Power supply:

Electrical power rating: Effective fog throwing range: Droplet size dependent on

nozzle size used:

Flow rate:

59 x 35 x 37 cm

6,6 kg net, 8,3 kg gross

nominal 5 Liter

230 V AC / 50-60 Hz or 110 V AC / 50-60 Hz

1,2 kW Up to 25 m

10 to 100 µm

Up to 48 L/h (800 ml/min)

A CONTROL OF THE PARTY OF THE P

The *Turbo ULV* is a portable AC powered pneumatic cold fogger. Its high performance turbine creates a powerful air stream of up to 50 l/s. The active solution is atomised into a fine aerosol, which is adjustable from approx. 10 to 100 µm depending on the flow rate setting. The precise flow regulation is provided by means of interchangeable nozzles. Chemical resistant materials assure long life and high performance for professional fogging jobs.

Main features:

- Trouble free and simple operation.
- High mobility due to small dimensions, low weight and extended fogging tube.
- Detachable solution tank for easy filling and cleaning.
- Allows space spray and/or residual applications.
- High efficiency air filter protects the motor and internal components.
- Sturdy construction for professional use.

Subject to technical changes 07/2020



pulsFOG Dr. Stahl & Sohn GmbH

Abigstraße 8 • D-88662 Überlingen • Tel. (0) 7551 / 9261-0 • Fax (0) 7551 / 926161 E-Mail: sales@pulsfog.com • Internet: http://www.pulsfog.com